

AMENDMENT TO THE CLAIMS

1. Cancelled

2. (Currently Amended) A double-hung window having an open position and a closed position, wherein the double-hung window comprises:

a first side jamb and a second side jamb, each side jamb ~~having~~comprising an upper side jamb, ~~and a lower side jamb, an interior extension slot, an exterior extension slot and a lock pin slot;~~

a head jamb;

an upper sash held in the window by the first and second upper side jambs and head jamb when the window is in the closed position;

a lower sash having a lock pin extendable from each side of the lower sash into the lock pin slot of its respective side jamb, the lower sash held in the window by the first and second lower side jambs when the window is in the closed position;

a concealed jamb liner cover for selective engagement with each upper side jamb, each jamb liner cover extending over the interior extension slot and lock pin slot at its respective upper side jamb, and each jamb liner cover having an exposed wood surface and having a channel for receiving the lock pin of the lower sash, allowing slidable movement of the lower sash.

3. (Original) The double-hung window of claim 2, wherein each concealed jamb liner cover comprises:

a profile having a first side and a second side, the first side selectively engages with the double-hung window; and

a wood veneer layer attached to the second side of the profile to form the exposed wood surface.

4. (Original) The double-hung window of claim 3, wherein the profile is extruded vinyl.
5. (Original) The double-hung window of claim 2, wherein the upper sash has an upper portion and further comprising:
  - an upper sash lock housing attached to the upper portion of the upper sash, wherein the upper sash lock housing holds a lock pin for each side of the upper sash.
6. (Original) The double-hung window of claim 5, further comprising:
  - an interior upper parting stop attached to the head jamb, wherein the upper parting stop conceals the upper sash latch housing when the upper sash is in the closed position.
7. (Original) The double-hung window of claim 6, wherein the interior upper parting stop is wood.
8. (Original) The double-hung window of claim 6, wherein the upper sash lock housing holds a strip of interior weather-strip that contacts the interior upper parting stop when the upper sash is in the closed position.
9. (Original) The double-hung window of claim 5, wherein the upper sash lock housing holds a strip of exterior weather-strip that contacts an exterior mounting when the upper sash is in the closed position.
10. (Original) The double-hung window of claim 2, further comprising a pivot pin laterally projecting from each side of the lower sash, wherein the lock pins of the lower sash slide in a first plane along the first and second side jambs and the pivot pins of the lower sash slide in a separate

second plane of the first and second side jamb.

11. (Original) The double-hung window of claim 2, wherein the channel extends continuously along the exposed wood surface of each concealed jamb liner cover.

12. (Original) The double-hung window of claim 2, wherein each concealed jamb liner cover engages its respective first or second side jamb by a snap-fit lock.

13. (Original) A double-hung window having a uniform interior wood appearance wherein the window has an open position and a closed position, the double-hung window comprises:

- a first and second side jamb, each side jamb having an upper side jamb and a lower side jamb;

- a head jamb;

- an upper sash having a wood frame, the upper sash being held in the window by the first and second upper side jambs and head jamb when the window is in the closed position;

- a lower sash having a wood frame and a lock pin extendable from each side of the lower sash, the lower sash being held in the window by the first and second lower side jambs when the window is in the closed position;

- a concealed jamb liner cover for selective engagement with each upper side jamb, each jamb liner cover having an exposed wood surface and having a channel for receiving the lock pin of the lower sash, allowing slidable movement of the lower sash;

- an upper sash lock housing attached to an upper portion of the wood frame of the upper sash, wherein the upper sash lock housing holds an upper sash lock pin for each side of the upper sash; and

- a wooden interior upper parting stop connected to the head jamb having a length sufficient to conceal the upper sash lock housing when the window is in the

closed position.

14. (Original) The double-hung window of claim 13, wherein the lower sash has pivot pins laterally extending from each side of the lower sash and wherein the lock pins of the lower sash slide in a first plane along the first and second side jambs and the pivot pins of the lower sash slide in a separate second plane along the first and second side jambs.

15. (Original) The double-hung window of claim 13, wherein the channel extends continuously along the exposed woods surface of each concealed jamb liner cover.

16. (Original) The double-hung window of claim 13, wherein each concealed jamb liner cover engages its first or second side jamb by a snap-fit lock.

17. (Original) The double-hung window of claim 13, wherein the upper sash lock housing holds a strip of interior weather-strip that contacts the interior upper parting stop when the upper sash is in the closed position.

18. (Original) The double-hung window of claim 13, wherein the upper sash lock housing holds a strip of exterior weather-strip that contacts an exterior mounting when the upper sash is in the closed position.

19-23 (Canceled)

24. (New) A double-hung window, wherein the window has an open position and a closed position, the double-hung window comprises:

    a first side jamb and a second side jamb, each side jamb comprising an upper side jamb and a lower side jamb;

    an upper sash having a frame with a first surface finish appearance on an interior side thereof, the upper sash being held in the window by the first and second

upper side jambs when the window is in the closed position;  
a lower sash having a frame with the first surface finish appearance on an interior side thereof, and having a lock pin extendable from each side of the lower sash, the lower sash being held in the window by the first and second lower side jambs when the window is in the closed position; and  
a concealed jamb liner cover for selective engagement with each upper side jamb, each jamb liner cover having an exposed surface with the first surface finish appearance thereon and having a channel for receiving the lock pin of the lower sash, allowing slidable movement of the lower sash.

25. (New) The double-hung window of claim 24, wherein each side jamb comprises an interior extension slot, an exterior extension slot and a lock pin slot, and wherein each jamb liner cover extends over the lock pin slot and the interior extension slot of its respective upper side jamb.

26. (New) The double-hung window of claim 25, wherein the channel of the jamb liner cover is aligned over the lock pin slot of its respective side jamb.